

SAFETY DATA SHEET

SECTION 1: CHEMICAL PRODUCT and COMPANY IDENTIFICATION

<u>Product Name:</u> Ethyl acrylate 98%

Product Code: E04340

Supplier: Pfaltz & Bauer, Inc.

172 E. Aurora Street

Waterbury, CT 06708 USA

Phone: 203-574-0075

FAX: 203-574-3181

Emergency Phone: INFOTRAC, US: 1-800-535-5053

INFOTRAC, INTERNATIONAL: +1-352-323-3500

SECTION 2: HAZARDS IDENTIFICATION

<u>Statement of Hazard:</u> Environmentally hazardous, Flammable liquid, In use may form

flammable/explosive vapour-air mixture, Irritant, Respiratory irritant,

Skin sensitizer

Acute Health Hazard: Irritant to eyes, skin, mucous membranes and respiratory system.

May be harmful by ingestion, skin absorption and inhalation.

<u>Chronic Health Hazard:</u> Target organ effect

HMIS Rating: H: 2 F: 3 P: 0

NFPA Rating: H: 2 F: 3 R: 0

To the best of our knowledge, the toxicological properties of this chemical have not been thoroughly investigated. Use appropriate procedures and precautions to prevent or minimize exposure.

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):

Acute toxicity, dermal (Category 4), H312

Acute toxicity, inhalation (Category 4), H332

Acute toxicity, oral (Category 4), H302

Flammable liquids (Category 2), H225

Hazardous to the aquatic environment, chronic toxicity (Category 2), H411

Sensitization, skin (Category 1), H317

Serious eye damage/eye irritation (Category 2A), H319

Skin corrosion/irritation (Category 2), H315

Specific target organ toxicity, single exposure (Category 2), H371

Specific target organ toxicity, single exposure; Respiratory tract irritation (Category 3), H335

Pictogram:









Signal Word:

Danger

<u>Hazard Statement(s):</u> H225 Highly flammable liquid and vapor.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H371 May cause damage to organs.

H411 Toxic to aquatic life with long-lasting effects.

Precautionary Statement(s):

P210 Keep away from heat/sparks/open flames/hot surfaces. — No

smoking.

P240 Ground/bond container and receiving equipment. P260 Do not breathe dust/fume/gas/mist/vapors/spray. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P301+P312 IF SWALLOWED: call a POISON CENTER or doctor/physician

IF you feel unwell.

P302+P352 IF ON SKIN: wash with plenty of soap and water.

P304+P340 IF INHALED: Remove victim to fresh air and Keep at rest in

a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsina.

P333+P313 IF SKIN irritation or rash occurs: Get medical

advice/attention.

<u>Supplemental Statement(s):</u> EUH018 In use may form flammable/explosive vapour-air mixture

SECTION 3: COMPOSITION/INFORMATION on INGREDIENTS

Chemical Name: Ethyl acrylate 98%

Synonyms: Acrylic acid ethyl ester; Ethyl 2-propenoate

CAS Number: 140-88-5

MDL Number: MFCD00009188

EINECS Number: 205-438-8

Beilstein Registry Number: 773866

Molecular Formula: C5H8O2

Molecular Weight: 100.12

<u>Content:</u> As specified in product name.

SECTION 4: FIRST AID MEASURES

Eye Contact: Flush eyes with large amounts of water for fifteen minutes. Separate

eyelids with fingers. If irritation persists, seek medical attention.

Skin Contact: Wash skin with soap and water. If irritation persists, seek medical

attention.

<u>Ingestion:</u> Do not induce vomiting. Seek medical attention.

Inhalation: Move to a fresh air environment. Contact a physician if breathing

becomes difficult.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point (°C): -1

<u>Explosion Limits:</u> Lower, % by volume: 1.8

Upper, % by volume: 12.1

Auto Ignition

Not Available

Temperature (°C):

<u>Extinguishing Media:</u> Carbon dioxide, dry chemical powder, alcohol-resistant foam, or water

spray

<u>Protective Equipment:</u> Wear self-contained respirator and fully protective impervious suit.

Specific Hazards: May emit hazardous fumes under fire conditions. In use may form

flammable/explosive mixure.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Protection: Wear a self-contained breathing apparatus, rubber boots and gloves,

and disposable coveralls. Dispose of coveralls after use. Remove from ignition sources if safe to do so. Follow emergency response plan and

contact proper authorities if needed. Keep unprotected persons away.

Environmental Protection: Keep spills out of sewers and bodies of water. Dike and contain the spill

with inert material. Absorb on sand, vermiculite or diatomite. Transfer material to a container for disposal or recovery. Ventilate area and wash

spill site after material pickup is complete.

SECTION 7: HANDLING and STORAGE

Handling and Storage: Avoid breathing dust, vapor, mist or gas. Avoid contact with skin and

eyes. Avoid prolonged or repeated exposure. Use only in a chemical fume hood. Open and handle container with care. Keep ignition sources

away.

Store in a tightly closed container in a dry, well-ventilated place.

Sensitivities: Air, Light

Storage Temperature (°C): 2 to 8

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use product in a well ventilated area or under a fume hood. Use proper

lab equipment while handling this product. Keep away from incompatible materials for possible risk of hazardous reaction.

Eve Protection: Wear appropriate protective eyeglass or chemical safety goggles. Make

sure that there is an eyewash station in your vicinity.

Skin Protection: Wear impervious gloves and protective clothing.

Respiratory Protection: Use a NIOSH approved respirator when exposure limits are exceeded or

if irritation or other symptoms are experienced.

<u>Exposure Limits:</u> <u>Country</u> <u>Source</u> <u>Type</u> <u>Value</u>

USA ACGIH TWA 5 ppm
USA OSHA STEL 25 ppm

USA OSHA PEL Not Available

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

<u>Appearance:</u> Clear colorless liquid

Odor: Acrid

Odor Threshold: Not Available

Flash Point (°C): -1

<u>Auto Ignition</u>

Not Available

Temperature (°C):

UEL % by Volume: 12.1

LEL % by Volume: 1.8

Melting Point (°C): -71

Boiling Point (°C): 99-100

<u>Evaporation Rate:</u> Not Available

pH Value: Not Available

<u>Density (g/cm³):</u> 0.924

Refractive Index $(n^{20}D)$: 1.4060

<u>Viscosity:</u> Not Available

Solubility in Water: Slightly soluble, 1.5 g/L

Solubility in Other: Slightly soluble in EtOH, DMSO, Chloroform, Alcohol, Ethyl ether

Vapor Pressure (mmHq): 31

Vapor Density (Air=1): 3.5

SECTION 10: STABILITY and REACTIVITY

Stability: Stable under normal temperatures and pressures.

<u>Incompatibility:</u> Oxidizing agents, Peroxides

<u>Reactivity:</u> Product may react with incompatible materials to release other

hazardous substances.

<u>Conditions to Avoid:</u> Heat, flame, sparks, other ignition sources.

<u>Hazardous</u> Carbon oxides

Decomposition Products:

SECTION 11: TOXICOLOGICAL INFORMATION

AT0700000 RTECS Reference:

Target Organs: Liver, Kidney

800.00 Toxicity Data: Oral Rat LD50 mg/kg:

> 2997.00 Dermal Rabbit LD50 mg/kg: Intraperitoneal Rat LD50 mg/kg: 450.00

Inhalation Rat LC50, mg/m3 - h: 1414.00 - 4

National Toxicology Program (NTP) listed: Carcinogenicity:

Not Available

International Agency for Research on Cancer (IARC) listed: Not

Available

Not Available **Potential Symptoms:**

SECTION 12: ECOLOGICAL INFORMATION

Toxicity: Flathead minnow LC50: 2.50 mg/l - 2.50 hrs.

SECTION 13: DISPOSAL CONSIDERATIONS

Contact a licensed professional waste disposal service. Dispose in a manner consistent with federal, state and local environmental regulations.

SECTION 14: TRANSPORT INFORMATION

Ethyl Acrylate, Stabilized DOT Shipping Name:

UN1917 DOT UN Number:

Class 3 DOT Hazard Class:

PGII **DOT Packing Group:**

1000 lbs Reportable Quantity:

Ethyl Acrylate, Stabilized **IMDG Shipping Name:**

IMDG UN Number: UN1917

IMDG Hazard Class: Class 3

PGII **IMDG Packing Group:**

Marine Pollutant: No

<u>IATA Shipping Name:</u> Ethyl Acrylate, Stabilized

IATA UN Number: UN1917

IATA Hazard Class: Class 3

IATA Packing Group: PGII

SECTION 15: REGULATORY INFORMATION

United States

Toxic Substance Control Act (TSCA) listed: Yes

Superfund Amendments and Reauthorization Act (SARA 302) listed: No

Superfund Amendments and Reauthorization Act (SARA 311/312) listed: No

Superfund Amendments and Reauthorization Act (SARA 313) listed: Yes

European Union

European Inventory of Existing Chemical Substances (EINECS): 205-438-8

<u>Canada</u>

Canadian Domestic Substances List (DSL) listed: Yes

Canadian Non-Domestic Substances List (NDSL) listed: No

SECTION 16: OTHER INFORMATION

Date Prepared: 7/10/2019

The information above is presented in good faith. It is believed to be accurate and represents the best information currently available to us. However, we make no warranty with respect to such information and we assume no liability resulting from its use. The user should consider this information as a supplement to other information that may be available and make independent judgement to ensure proper use to protect the health and safety of employees and the environment. Pfaltz and Bauer shall not be held liable for any damage resulting from handling or from contact with the above product.