

## SECTION 1: CHEMICAL PRODUCT and COMPANY IDENTIFICATION

Product Name: 3-Methyl-2-butanone

Product Code: M13150

Supplier: Pfaltz & Bauer, Inc.  
172 E. Aurora Street  
Waterbury, CT 06708 USA

Phone: 203-574-0075

FAX: 203-574-3181

Emergency Phone: INFOTRAC, US: 1-800-535-5053  
INFOTRAC, INTERNATIONAL: +1-352-323-3500

## SECTION 2: HAZARDS IDENTIFICATION

Statement of Hazard: Flammable liquid, In use may form flammable/explosive vapour-air mixture, Irritant, Narcotic effects , Respiratory irritant

Acute Health Hazard: Irritant to eyes, skin, mucous membranes and respiratory system.  
May be harmful by ingestion, skin absorption and inhalation.

Chronic Health Hazard: Not Available

HMIS Rating: H: 2      F: 3      P: 0

NFPA Rating: H: 2      F: 3      R: 0

To the best of our knowledge, the toxicological properties of this chemical have not been thoroughly investigated. Use appropriate procedures and precautions to prevent or minimize exposure.

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):

GHS Classification in accordance with Regulation (EC) No 1272/2008:

Acute toxicity, dermal (Category 4), H312  
Acute toxicity, inhalation (Category 4), H332  
Acute toxicity, oral (Category 4), H302  
Flammable liquids (Category 2), H225  
Serious eye damage/eye irritation (Category 2A), H319  
Skin corrosion/irritation (Category 2), H315  
Specific target organ toxicity, single exposure; Narcotic effects (Category 3), H336  
Specific target organ toxicity, single exposure; Respiratory tract irritation (Category 3), H335

Pictogram:



Signal Word:

Danger

Hazard Statement(s):

H225 Highly flammable liquid and vapor.  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

Precautionary Statement(s):

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.  
P240 Ground/bond container and receiving equipment.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.  
P302+P352 IF ON SKIN: wash with plenty of soap and water.  
P304+P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P332+P313 IF SKIN irritation occurs: Get medical advice/attention.  
P403+P235 Store in a well-ventilated place. Keep cool.

Supplemental Statement(s):

EUH018 In use may form flammable/explosive vapour-air mixture

### **SECTION 3: COMPOSITION/INFORMATION on INGREDIENTS**

Chemical Name:

3-Methyl-2-butanone

Synonyms:

Isopropyl methyl ketone, Methyl isopropyl ketone; 3-Methyl butan 2-one

CAS Number:

563-80-4

MDL Number:

MFCD00008919

EINECS Number: 209-264-3

Beilstein Registry Number: 1071238

Molecular Formula: C<sub>5</sub>H<sub>10</sub>O

Molecular Weight: 86.13

Content: As specified in product name.

#### **SECTION 4: FIRST AID MEASURES**

Eye Contact: Flush eyes with large amounts of water for fifteen minutes. Separate eyelids with fingers. If irritation persists, seek medical attention.

Skin Contact: Wash skin with soap and water. If irritation persists, seek medical attention.

Ingestion: Do not induce vomiting. Seek medical attention.

Inhalation: Move to a fresh air environment. Contact a physician if breathing becomes difficult.

#### **SECTION 5: FIRE FIGHTING MEASURES**

Flash Point (°C): -3

Explosion Limits: Lower, % by volume: Not Available  
Upper, % by volume: 8.2

Auto Ignition Temperature (°C): Not Available

Extinguishing Media: Carbon dioxide, dry chemical powder, alcohol-resistant foam, or water spray

Protective Equipment: Wear self-contained respirator and fully protective impervious suit.

Specific Hazards: May emit hazardous fumes under fire conditions. In use may form flammable/explosive mixture.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Personal Protection: Wear a self-contained breathing apparatus, rubber boots and gloves, and disposable coveralls. Dispose of coveralls after use. Remove from ignition sources if safe to do so. Follow emergency response plan and contact proper authorities if needed. Keep unprotected persons away.

Environmental Protection:

Keep spills out of sewers and bodies of water. Dike and contain the spill with inert material. Absorb on sand, vermiculite or diatomite. Transfer material to a container for disposal or recovery. Ventilate area and wash spill site after material pickup is complete.

## SECTION 7: HANDLING and STORAGE

Handling and Storage:

Avoid breathing dust, vapor, mist or gas. Avoid contact with skin and eyes. Avoid prolonged or repeated exposure. Use only in a chemical fume hood. Open and handle container with care. Keep ignition sources away.  
Store in a tightly closed container in a dry, well-ventilated place.

Sensitivities:

Air

Storage Temperature (°C):

2 to 8

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

Use product in a well ventilated area or under a fume hood. Use proper lab equipment while handling this product. Keep away from incompatible materials for possible risk of hazardous reaction.

Eye Protection:

Wear appropriate protective eyeglass or chemical safety goggles. Make sure that there is an eyewash station in your vicinity.

Skin Protection:

Wear impervious gloves and protective clothing.

Respiratory Protection:

Use a NIOSH approved respirator when exposure limits are exceeded or if irritation or other symptoms are experienced.

Exposure Limits:

| <u>Country</u> | <u>Source</u> | <u>Type</u> | <u>Value</u>  |
|----------------|---------------|-------------|---------------|
| USA            | ACGIH         | TWA         | 200 ppm       |
| USA            | OSHA          | STEL        | Not Available |
| USA            | OSHA          | PEL         | Not Available |

## SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Appearance:

Clear colorless liquid

Odor:

Pleasant

Odor Threshold:

Not Available

Flash Point (°C):

-3

Auto Ignition  
Temperature (°C):

Not Available

|                                            |                           |
|--------------------------------------------|---------------------------|
| <u>UEL % by Volume:</u>                    | 8.2                       |
| <u>LEL % by Volume:</u>                    | Not Available             |
| <u>Melting Point (°C):</u>                 | -92                       |
| <u>Boiling Point (°C):</u>                 | 94-95                     |
| <u>Evaporation Rate:</u>                   | Not Available             |
| <u>pH Value:</u>                           | Not Available             |
| <u>Density (g/cm<sup>3</sup>):</u>         | 0.805                     |
| <u>Refractive Index (n<sup>20D</sup>):</u> | 1.388                     |
| <u>Viscosity:</u>                          | Not Available             |
| <u>Solubility in Water:</u>                | Soluble, 8.21 g/L at 20 C |
| <u>Solubility in Other:</u>                | Not Available             |
| <u>Vapor Pressure (mmHg):</u>              | Not Available             |
| <u>Vapor Density (Air=1):</u>              | Not Available             |

## SECTION 10: STABILITY and REACTIVITY

|                                          |                                                                                      |
|------------------------------------------|--------------------------------------------------------------------------------------|
| <u>Stability:</u>                        | Stable under normal temperatures and pressures.                                      |
| <u>Incompatibility:</u>                  | Strong oxidizing agents, Strong bases, Strong reducing agents                        |
| <u>Reactivity:</u>                       | Product may react with incompatible materials to release other hazardous substances. |
| <u>Conditions to Avoid:</u>              | Heat, flame, sparks, other ignition sources.                                         |
| <u>Hazardous Decomposition Products:</u> | Carbon oxides                                                                        |

## SECTION 11: TOXICOLOGICAL INFORMATION

|                         |               |
|-------------------------|---------------|
| <u>RTECS Reference:</u> | EL9100000     |
| <u>Target Organs:</u>   | Not Available |

|                       |                                                          |             |
|-----------------------|----------------------------------------------------------|-------------|
| <u>Toxicity Data:</u> | Oral Rat LD <sub>50</sub> mg/kg:                         | 3078.00     |
|                       | Dermal Rabbit LD <sub>50</sub> mg/kg:                    | 6350.00     |
|                       | Inhalation Rat LC <sub>50</sub> , mg/m <sup>3</sup> – h: | 6377.00 – 6 |

|                         |                                                                          |
|-------------------------|--------------------------------------------------------------------------|
| <u>Carcinogenicity:</u> | National Toxicology Program (NTP) listed:<br>Not Available               |
|                         | International Agency for Research on Cancer (IARC) listed: Not Available |

|                            |               |
|----------------------------|---------------|
| <u>Potential Symptoms:</u> | Not Available |
|----------------------------|---------------|

## SECTION 12: ECOLOGICAL INFORMATION

|                  |                                    |                           |
|------------------|------------------------------------|---------------------------|
| <u>Toxicity:</u> | Rainbow trout LC <sub>50</sub> :   | 68.00 mg/l - 96 hrs.      |
|                  | Flathead minnow LC <sub>50</sub> : | 918.00 mg/l - 918.00 hrs. |
|                  | Water flea LC <sub>50</sub> :      | 100.00 mg/l - 100.00 hrs. |

## SECTION 13: DISPOSAL CONSIDERATIONS

Contact a licensed professional waste disposal service. Dispose in a manner consistent with federal, state and local environmental regulations.

## SECTION 14: TRANSPORT INFORMATION

|                           |                     |
|---------------------------|---------------------|
| <u>DOT Shipping Name:</u> | 3-Methylbutan-2-one |
|---------------------------|---------------------|

|                       |        |
|-----------------------|--------|
| <u>DOT UN Number:</u> | UN2397 |
|-----------------------|--------|

|                          |         |
|--------------------------|---------|
| <u>DOT Hazard Class:</u> | Class 3 |
|--------------------------|---------|

|                           |      |
|---------------------------|------|
| <u>DOT Packing Group:</u> | PGII |
|---------------------------|------|

|                            |                     |
|----------------------------|---------------------|
| <u>IMDG Shipping Name:</u> | 3-Methylbutan-2-one |
|----------------------------|---------------------|

|                        |        |
|------------------------|--------|
| <u>IMDG UN Number:</u> | UN2397 |
|------------------------|--------|

|                           |         |
|---------------------------|---------|
| <u>IMDG Hazard Class:</u> | Class 3 |
|---------------------------|---------|

|                            |      |
|----------------------------|------|
| <u>IMDG Packing Group:</u> | PGII |
|----------------------------|------|

|                          |    |
|--------------------------|----|
| <u>Marine Pollutant:</u> | No |
|--------------------------|----|

|                            |                     |
|----------------------------|---------------------|
| <u>IATA Shipping Name:</u> | 3-Methylbutan-2-one |
|----------------------------|---------------------|

|                        |        |
|------------------------|--------|
| <u>IATA UN Number:</u> | UN2397 |
|------------------------|--------|

IATA Hazard Class:

Class 3

IATA Packing Group:

PGII

## **SECTION 15: REGULATORY INFORMATION**

### United States

Toxic Substance Control Act (TSCA) listed: Yes

Superfund Amendments and Reauthorization Act (SARA 302) listed: No

Superfund Amendments and Reauthorization Act (SARA 311/312) listed: No

Superfund Amendments and Reauthorization Act (SARA 313) listed: No

### European Union

European Inventory of Existing Chemical Substances (EINECS): 209-264-3

GHS Classification in accordance with Regulation (EC) No 1272/2008: Yes

### Canada

Canadian Domestic Substances List (DSL) listed: Yes

Canadian Non-Domestic Substances List (NDSL) listed: No

## **SECTION 16: OTHER INFORMATION**

Date Prepared: 6/21/2023

The information above is presented in good faith. It is believed to be accurate and represents the best information currently available to us. However, we make no warranty with respect to such information and we assume no liability resulting from its use. The user should consider this information as a supplement to other information that may be available and make independent judgement to ensure proper use to protect the health and safety of employees and the environment. Pfaltz and Bauer shall not be held liable for any damage resulting from handling or from contact with the above product.